

UR-110 PT - Perfection is in the detail.

Geneva – January 2013

The UR-110 is back on the scene, shedding its original titanium and steel case to retain the essentials: Its ARCAP mainplate and planetary satellite complication. The UR-110 has got a second wind and with it, a platinum bezel for a decidedly vintage look.









The technical complexity of the UR-110 collection is based on:

- A central carousel providing the complication with stability and equilibrium
- Planetary gearing assuring the parallel rotation of the three hour satellites as they orbit the dial
- The three counter-rotating hour modules each comprising an hour satellite, minute hand and counter balance are each mounted on a planetary gear. These three modules are in constant counter-rotation to counter the direction of rotation of the central carousel.

The UR-110's technology can be appreciated through the large panoramic sapphire crystal. As well as indicating the hours and minutes, the UR-110 also features a Control Board on the dial side with indicators for "Day/Night" and "Oil Change" — URWERK's service interval display — as well as small seconds on a sub dial. Turning the watch over, the titanium back encloses the innovative automatic winding system regulated by dual turbines.



UR-110 PT Technical Specifications

Case

Case in Grade 5 titanium with platinum bezel (limited edition of 20 pieces)

Dimensions: 47mm x 51mm x 16mm

Two position crown with integrated protection

Water resistance: 3 ATM

Mouvement

Calibre: UR 9.01 mechanical, automatic winding

Balance: Monometallic Frequency: 28,800v/h, 4Hz

Jewels: 46

Balance spring: Flat

Power: Single barrel

Power reserve: 39 hours

Winding system: Uni-directional rotor regulated by double turbines

Finishing: Satin finishing, spotting et diamond polishing

Indications

Satellite complication with rotating hour/minute modules mounted on planetary gears

Control Board: "Day/Night" indicator; "Oil Change" alerting service intervals and small seconds

Media contact

Ms Yacine Sar – URWERK S.A.

press@urwerk.com

mob: +41 79 834 46 65